

Enlouva IV

CONFIGURATION SPECIFICATIONS

SECTIONS <small>(plus main)</small>	ARM	REACH	HEIGHT	MAXIMUM	WEIGHT
6Ft	3Ft.	FEET	FEET	WEIGHT	RATIO
(2)	(1)	22' - 6"	23' - 6"	148 lbs	3.86/1
(2)	-	19' - 6"	21' - 0"	198 lbs	3.34/1
(1)	(1)	16' - 6"	18' - 6"	260 lbs	2.83/1
(1)	-	13' - 6"	16' - 0"	340 lbs	2.31/1
-	(1)	10' - 6"	13' - 6"	451 lbs	1.80/1
MAIN ONLY		7' - 6"	11' - 0"	664 lbs	1.29/1

ARM MEASUREMENTS

Arm Length	28' - 4"
Arm Width	11"
Arm Height	7"
Doorway Clearance (H)	6' - 9"
Doorway Clearance (W)	58"

TERRAIN SPECS

Wheel Base Width	58"
Track Width	35"
Arm Mount	MITCHELL
Steering	DUAL/CRAB
Outriggers	4



ENLOUVA IV &
FISHER 23

Fisher 23

CONFIGURATION SPECIFICATIONS

Version	Max. Payload	Max. Height	Min. Height	Unladen Height
1	200 lbs.	8'-9"	2'-3"	189 lbs.
2	200 lbs.	11'-2"	1" below ground level	207 lbs.
3	200 lbs.	11'-2"	1" below ground level	237 lbs.
4	200 lbs.	13'-6"	2'-4" below ground level	271 lbs.
5	200 lbs.	15'-10"	4'-8" below ground level	297 lbs.
6	187 lbs.	18'-3"	7' below ground level	319 lbs.
7	131 lbs.	20'-7"	9'-4" below ground level	340 lbs.

